

## HPfC Hardmill

### High Performance Coating for Hard Machining

#### HPfC Hardmill


is designed for machining hardened steel (> 52 HRC) in dry or mist lubricant conditions.

The coating is based on a AlTiCrSiN multilayer structure.


Versions with optimized coating composition and thickness for roughing, finishing and microtools are available.

#### Performances:


##### HPfC Hardmill






##### Competitor A



##### Competitor B



wear after 30 meter machining  
hard machining D2 at 60 HRC  
dia 8 mm; Vc 200 m/min; fz 0,12 /tooth, ap 3 mm; ae 0,5 mm; dry air blow



## Increase the Performance of Your Hard Machining Tools



*Increase your  
Competitiveness!*

#### Properties

- high heat resistance at the cutting edge
- hot hardness
- very high oxidation resistance (>1100°C)
- low thermal conductivity

Contact us at: [www.performcoat.com](http://www.performcoat.com)

#### for Europe:

PerformCoat Germany  
Ferdinand-Porsche-Str. 10  
88451 Dettingen-Iller Germany  
[pierre.collignon@performcoat.eu](mailto:pierre.collignon@performcoat.eu)  
Tel. +33 676 332598

#### for Americas:

PerformCoat of North America  
319 McIntyre Lane  
Springfield, Mi 49037 US  
[info@performcoat.com](mailto:info@performcoat.com)  
Tel. +1 865 321 3932

#### for Japan:

Nobu Fujita  
324-4 Nozomigaoka  
Meitu-ku 465-0046 Nagoya Japan  
[fujita@seibushoko.com](mailto:fujita@seibushoko.com)  
Tel. +81 90 9043 5385

#### for Rest of Asia:

PerformCoat of Asia  
6F, No.348, Sec.7,  
Chengteh Rd. Taipei, Taiwan  
[gary.sonic@msa.hinet.net](mailto:gary.sonic@msa.hinet.net)  
Tel. +886 (02) 28 28 27 50